dLAN 200 AV

Technical data

Standards	▪ Ethernet specifications IEEE 802.3, IEEE 802.3x, IEEE 802.3u, Auto MDI / X ▪ HomePlug AV
Protocols	TDMA, CSMA/CA
Transmission speed	200 Mbps
Transmission method	asynchronous
Modulation	OFDM - 1155 carriers, 1024/256/64-QAM, QPSK, BPSK
Data path	▪ Ethernet <-> power supply grid
Range	▪ up to 200m over household power supply grid
Security	128-bit AES encryption over household power supply grid
LEDs	▪ Power ▪ Ethernet (Link/Act) ▪ dLAN (Link/Act)
dLAN port	▪ UK plug
Device port	▪ Ethernet RJ45
Power consumption	5.5 W (max.)
Power supply	AC 100-240V 50/60Hz
Weight	165 g
Dimensions	80 x 65 x 40 mm (height x width x depth)
Temperature	Storage: –25℃ – 70℃ Operation: 0℃ – 40℃
Ambient conditions	10–90% humidity (non-condensing)
System requirements	Ethernet port
Operating systems	Windows® 98, Windows® ME, Windows® 2000, Windows® XP, Linux®, Mac OS® X and all operating systems with TCP/IP support
Certifications	CE-compliant in accordance with the technical requirements of all EU countries and Switzerland: EN 55022 EN 50412 EN 60950

Sales information

Article number	01171 (UK)
EAN-Code	4250059611719 (UK)
Warranty	3 years
Service & Support	Telephone and e-mail support. Please see the included support flyer or the devolo website for telephone numbers and e-mail addresses.
Design	Plastic wallplug housing
Weight	440 g
Package dimensions	78,5 x 231 x 188,5 mm (height x width x depth)
Accessories	▪ Ethernet cable RJ45-RJ45 (Cat 5) ▪ Documentation: printed installation guide ▪ CD-ROM: PDF manual, configuration software for Windows®, Linux®, Mac OS® X, Additional software: devolo Informer, devolo EasyShare, devolo EasyClean

devolo UK
PO Box 1434
Oxford
OX4 9AW
Tel.: +44 (0) 1865 244141
E-mail: sales@devolo.co.uk
Internet: www.devolo.co.uk

devolo AG
Sonnenweg 11
52070 Aachen
Tel.: +49 (0) 241 18279 79
Fax: +49 (0) 241 18279 99
email: info@devolo.com
Internet: www.devolo.com

Status: 26/06/2007